

BUSINESS BROCHURE
EV CHARGER

KEVO
POWER



www.kevopower.com

AC SERIES II

Standard Fast EV Charger

AC Portable 3.5/7/11/22KW

KP-A3S-II


KP-A7S-II

KP-A11S-II

KP-A22S-II



Key Benefits



Overvoltage
Protection



Undervoltage
Protection



Lightning
Protection



IP65



Overtemperature
Protection



Fully
Certified



Grounded/
Ungrounded



HCI



Overcurrent
Protection



OTA



Bluetooth/
WIFI



Leakage
Protection

PRODUCT PARAMETERS

Model	KP-A3S-II	KP-A7S-II	KP-A11S-II	KP-A22S-II
Output Power	3.5KW	7KW	11KW	22KW
Overcurrent Protection	≥110% of rated output			
Operating Voltage	230Vac±15%			
Leakage Protection	AC/A+DC6mA			
Output Current(max)	16A	32A	16A	32A
CP voltage protection	±1V			
Operating Frequency	50/60Hz			
Overtemperature Protection	85℃ (protection) / 65℃ (resumption)			
Rated charging Current (max)	16A(max)	32A(max)	16A(max)	32A(max)
Lightning Protection	Yes (Supported)			
Rated Input/ Output Voltage	230Vac		400Vac	400Vac
Relay Sticking	Yes (Supported)			
Operating Temperature	-25℃ ~+50℃			
Grounding	Yes (Supported)			
Storage Temperature	-40℃ ~+60℃			
Undervoltage Protection	≤85V			
Overvoltage Protection	≥270V			
Waterproof Rating	IP65			
HCI	Touch Key + 2.8 Inch Display			
Body Size	225*80*56 mm			
Package Size	400*360*95 mm			
Output Line Length	5 m			
Input Line Length	0.5 m			



3.5KW



7KW



11KW



22KW



KEVO POWER - EV Charger Solutions Provider

Online: kevopower.com

Email: info@kevopower.com

WhatsApp: +86 15986673554

Address: Tianlilai Industrial Park, Dalingshan, Dongguan City,
Guangdong Province, China

