

BUSINESS BROCHURE
EV CHARGER

KEVO
POWER



www.kevopower.com

AC SERIES III

Standard Fast EV Charger

AC 7KW 11KW 22KW

KP-A7S-III

KP-A11S-III

KP-A22S-III



Key Benefits



Overvoltage
Protection



Undervoltage
Protection



Overcurrent
Protection



OTA



Grounded/
Ungrounded



HCI



Overtemperature
Protection



Lightning
Protection



IP65



Bluetooth/
WIFI



Leakage
Protection



Fully
Certified

PRODUCT PARAMETERS

Model	KP-A7S-III	KP-A11S-III	KP-A22S-III
Output Power	7KW	11KW	22KW
Operating Voltage	230Vac±15%		
Overcurrent Protection	≥110% of rated output		
Output Current(max)	32A	16A	32A
Leakage Protection	A/A+DC6mA		
Operating Frequency	50/60Hz		
CP voltage protection	±1V		
Rated charging Current (max)	32A(max)	16A(max)	32A(max)
Overtemperature Protection	85 ℃ (protection) / 65 ℃ (resumption)		
Rated Input/ Output Voltage	230Vac	400Vac	400Vac
Lightning Protection	Yes (Supported)		
Operating Temperature	-25 ℃ ~+50 ℃		
Relay Sticking	Yes (Supported)		
Storage Temperature	-40 ℃ ~+60 ℃		
Grounding	Yes (Supported)		
Overvoltage Protection	≥270V		
Undervoltage Protection	≤85V		
HCI	4.3 Inch Display		
Waterproof Rating	IP65		
Package Size	530*260*255 mm		
Body Size	400*163*95 mm		
Input Line Length	1 m		
Output Line Length	5 m		



Pragmatic



Indicator light: green always on



Charge Waiting



Indicator light: blue always on



Charging Complete



Indicator light: blue always on



Insert A Gun



Indicator light: green flashing



Charging



Indicator light: blue flashing



Faults



Indicator light: red flashing



KEVO POWER - EV Charger Solutions Provider

Online: kevopower.com

Email: info@kevopower.com

WhatsApp: +86 15986673554

Address: Tianlilai Industrial Park, Dalingshan, Dongguan City,
Guangdong Province, China

