

BUSINESS BROCHURE
EV CHARGER

KEVO
POWER



www.kevopower.com

DC SERIES II

Standard Fast EV Charger

DC 20KW 30KW 40KW Single Guns

KP-D40S-II



7-inch Color Touch Screen

User-friendly interface with crisp visuals for an effortless charging experience.



4G / Ethernet / WIFI

Flexible multi-mode network communication for stable, real-time remote management.



Communication Protocol: OCPP 1.6J / 2.0.1

Seamless smart connectivity and backend integration powered by universal OCPP 1.6J protocol.



IP Grade: IP55 Waterproof

Robust IP55 waterproof protection, engineered to withstand heavy rain and dust.



Modular Design for Maintenance

Simplified maintenance and independent power module replacement, minimizing station downtime.



Noise: ≤65db

Ultra-quiet operation at ≤65dB, perfect for quiet residential and commercial zones.



Working Temperature: -30°C to 70°C

All-weather durability, performing flawlessly in extreme climates from -30°C to 70°C.

PRODUCT PARAMETERS

Model	KP-D20S-II	KP-D30S-II	KP-D40S-II
Input voltage	AC380V Three-phase five-wire		
Input voltage range	380Vac±20%		
Maximum input current	32A	58A	76A
Operating frequency	50/60Hz		
Output voltage range	50-1000VDC		
Maximum output	63A	100A	133A
Output power	20KW	30KW	40KW
Power switching			
THDi	≤5% (Input 380V, Output 1000V, 50%-100% Load)		
Input surge current	≤110% of rated input current		
Power factor	≥0.99 (50%-100% output power, nominal input voltage and frequency)		
	≥0.95 (20%-50% output power, nominal input voltage and frequency)		
Voltage regulation	≤±0.5% (-30℃~+55℃)		
Current stabilization	≤±1% (-30℃~+55℃, 20%-100%Load current)		
Output ripple	Ripple peak coefficient ≤ ±1% (input voltage at 85%, 100%, 115%)		
Overall machine efficiency	≥96% (100% full load output power)		
Standby power consumption	≤15W		
Heat dissipation	air-cooled		
Noise	≤75db(1 meter away)		
Cable specifications	Cu : 3*10+2*6mm ²	Cu : 3*16+2*10mm ²	Cu : 3*25+2*16mm ²
	Al : 3*25+2*16mm ²	Al : 3*25+2*16mm ²	Al : 3*35+2*25mm ²
Relevant standards	Meets technical requirements:GB/T 18487.1-2015; GB/T 27930-2015; GB/T 20234-2015		
Charging Gun	5m charging gun (length customized available)		





KEVO POWER - EV Charger Solutions Provider

Online: kevopower.com

Email: info@kevopower.com

WhatsApp: +86 15986673554

Address: Tianlilai Industrial Park, Dalingshan, Dongguan City,
Guangdong Province, China

