


BUSINESS BROCHURE
EV CHARGER



DC SERIES X

Standard Fast EV Charger

DC 320KW 360KW 400KW

KP-D400D-X



Optional

32-inch Advertising Screen

Double your revenue with a 32-inch ad screen that turns charging time into high-impact marketing prime time.



4G / Ethernet / WIFI

Flexible multi-mode network communication for stable, real-time remote management.



Communication Protocol: OCPP 1.6J / 2.0.1

Seamless smart connectivity and backend integration powered by universal OCPP 1.6J protocol.



IP54 Waterproof & Noise: ≤75db

Built for the elements and quiet spaces alike. It delivers robust IP54 defense against rain and dust and runs quietly at under 75dB for commercial and residential comfort.



Modular Design for Maintenance

Simplified maintenance and independent power module replacement, minimizing station downtime.



Power Assisted Arm

Ergonomic gravity compensation minimizes lifting effort for easy plugging. Flexibly rotates to extend reach and automatically retracts to prevent cable wear.



Working Temperature: -30°C to 70°C

All-weather durability, performing flawlessly in extreme climates from -30°C to 70°C.



PRODUCT PARAMETERS

Model	KP-D320D-X		KP-D360D-X	KP-D400D-X
Rated Input Voltage	AC380 V three-phase five-wire			
Input Voltage Range	380 VAC ±20 %			
Maximum Input Current	640 A (320A/every route)		720 A (360A/every route)	800 A (400A/every route)
Operating Frequency	50/60 Hz			
Output Voltage Range	50–1000 V DC			
Maximum Output Current	250 A			
per Gun/Connector				
Rated Output Power	320 kW		360 kW	400 kW
Power Allocation/Switching	Equal power sharing			
Total Harmonic Distortion of Input Current (THDI)	THDI ≤5 % (input 380 V, output 1000 V, 50 %–100 % load)			
Input Inrush Current	Inrush current ≤110 % of rated input current			
Power Factor (PF)	Power factor 0.99 (50 %–100 % output power, nominal input voltage & frequency) Power factor 0.95 (20 %–50 % output power, nominal input voltage & frequency)			
Voltage Regulation Accuracy	Voltage regulation ±0.5 % (-30 °C to +55 °C)			
Current Regulation Accuracy	Current regulation ±1 % (-30 °C to +55 °C, 20 %–100 % load current)			
Output Voltage Ripple	Output voltage ripple peak coefficient ±1 % (input voltage 85 %, 100 %, 115 %)			
Overall Efficiency	Efficiency ≥96 % (100 % full-load output power)			
Standby Power Consumption	Standby power ≤15 W			
Cooling Method	Cooling method: forced air			
Communication Protocol	OCPP 1.6J /2.0.1			
Charging Gun	5m charging gun (length customized available)			
Communication Interface	4G / Ethernet / WIFI			
IP Grade	IP54			
Working Temperature	-30 °C ~ 70 °C			
Cable Specification Reference	Cu: 3×120mm ² +2×70mm ² Al: 13×185mm ² +2×120mm ²		Cu: 3×150mm ² +2×95mm ² Al: 3×240mm ² +2×150mm ²	Cu: 3×185mm ² +2×120mm ² Al: 3×300mm ² +2×240mm ²
Relevant Standards	GB/T 18487.1-2015; GB/T 27930-2015; GB/T 20234-2015			
Package Size	1050*1200*2360mm			
Gross Weight	486.5kg (400KW)			





KEVO POWER - EV Charger Solutions Provider

Online: kevopower.com

Email: info@kevopower.com

WhatsApp: +86 15986673554

Address: Tianlilai Industrial Park, Dalingshan, Dongguan City,
Guangdong Province, China

